

## Material Datasheet

Article name	<b>High quality paper labels</b>
Article No.	<b>Paper, machine coated, white, glossy, permanent</b> PCL3-MCG, PCL3-2551MCG, PCL3-6233MCG, PCL3-8045MCG, PCL3-9651MCG, PCL3-94140MCG, PCL3-75110MCG, PCL3-25MCG, PCL3-37MCG, PCL3-51MCG, PCL3-64MCG, PCL3-MCGBS
SAP Code	2438

<b>Face material</b>	
Material description	White, wood-free, machine coated, glossy paper
Basis weight	90g/m <sup>2</sup>
<b>Adhesive</b>	
Type	Permanent acrylic emulsion adhesive
Food contact	The adhesive can be used in indirect food contact.
<b>Release liner</b>	
Type	White kraft paper
<b>Laminate</b>	
Caliper	172µm
Basis Weight	190g/m <sup>2</sup>
Service temperature	-10 °C to +65 °C
Minimum application temperature	0 °C
Shelf life	2 years under storage conditions as specified by FINAT Part 2.5 (20 – 25 °C, 40 – 50% RH)
<b>Printing</b>	
	Suitable for Offset, Laserprinter und Copiers (digital) and HP Indigo
<b>Packaging</b>	
Material	100 sheet box (1050 g/m <sup>2</sup> )

Note: All data to be considered as typical values.