



## Material Datasheet

Article name	<b>High quality paper labels</b> <b>Paper, machine-finished, cream, narrow-ribbed, permanent</b>
Article No.	PCL3-AWL, PCL3-75110AWL, PCL3-51AWL
SAP Code	117285, 117286, 117287

<b>Face material</b>	
Material description	Cream, wood-free, narrow-ribbed, machine finished, wet-strength paper that is alkali resistant and mould proof
Basis weight	90g/m <sup>2</sup>
<b>Adhesive</b>	
Type	Permanent acrylic emulsion adhesive
Performance	The permanent adhesive provides good adhesion in water, is cold and heat proof and best suited for applications on curved surfaces
<b>Release liner</b>	
Type	White kraft paper
<b>Laminate</b>	
Caliper	210µm
Basis Weight	200g/m <sup>2</sup>
Service temperature	-20°C to +80°C
Minimum application temperature	5°C
Recommended storage	20°C, 50% RH. Protect from light.
Shelf life	1 year under storage conditions as specified above
<b>Printing</b>	
	Suitable for Offset, Laserprinter und Copiers (digital) and HP Indigo
<b>Packaging</b>	
Material	100 sheet box (1050 g/m <sup>2</sup> )

Note: All data to be considered as typical values.